

DK-235SB/240SB

TWO POST LIFT



- 1 Tray.
- 2 Setting insurance regulation hole, easy to repair and maintenance.
- 3 Adopt hot dip galvanized and special process 6 core 19 strand wire rope, anti-rust and anti-off the wire.
- 4 Mn steel BL644 each section 4 * 4 chain.
- 5 Hydraulic cylinder process to create a mirror polished surface, to achieve the level of mirror.
- 6 Slide square tube adopts 5mm international standard.
- 7 GB Q235 16mm.
- 8 Solid 25mm toe board.
- 9 Q235 international 16mm board.
- 10 Q235 international 4mm checkered plate, and bottom with angle iron welded reinforcement, so that car would not deformed.
- 11 6mm (inside and outside) tube thickness.
- 12 SS400 international standards 5mm open flat column.



✓ Standard

◇ Optional

Model	DK-235SB/DK-240SB
Capacity(KG)	3500/4000
lift Height(MM)	1900
Rise Time(S)	50
Drop Time(S)	22
Power Supply(V)	380/220
Motor Power(KW)	2.2

Swing Arm		Tray		Other Optional Accessories									
Straight arm plus bend arm	✓	Four Straight arm	✓	Two joint round tray	◇	Octagonal tray	◇	Simple control box	◇	Up limit switch	◇	Protected foot guard bar	◇
						  							